

Product information RA 220 high-power industrial suction unit

- » continuous suction power with 24h operation possible, quiet, low-maintenance, can also be used as a stationary unit
- » filter tank with bag filter 1.75m², CAT "L", "M"
- » running gear in sturdy welded rectangular tube design
- » various filter qualities available



Features



run-out collection tank with easy release



Inspection glass integrated in collection tank



Powerful drives, direct drive side-channel compressor



Sturdy steering castors with stopper and ram protection



RA 220 in EX design for the pharmaceuticals industry

RA 220



High-power industrial suction unit

For versatile uses, e.g. in the metal-processing industry. Direct drive side-channel compressor; filter classes L, M, H depending on application. Effective and continuous filter technology. Suitable for the suction extraction of carcinogenic dusts, chips, granulate.

Technical data for the series RA 220

| Suction unit type | RA 220 D5,5 | RA 220 D2x3 |
|---|---------------------|---------------------|
| Output [kW] | 5,5 | 6,0 |
| Voltage [V] | 400 | 400 |
| Max. vacuum [kPa] | 26 | 32 |
| Max. air flow rate [Nm ³ /h] | 520 | 640 |
| Sound level dB [A] | 69 | 70 |
| Dimensions [mm] | 1.690 x 760 x 1.507 | 1.690 x 760 x 1.507 |
| Weight [kg] | 243 | 235 |
| Article number | 990 0234 | 990 0937 |