

Product information RI 131 a.c. suction unit

- » suction cleaner suitable for the suction extraction of particulate matter
- » can be used in production facilities and warehouses
- » simple, effective filter cleaning
- » long filter service lives, filter can be washed
- » bag filter for efficient and uninterrupted suction

Features



Shaker lever for effective filter cleaning



Collection tank release



Run-out collection tank, the filter does not have to be removed

RI 131



Industrial / trade suction cleaner with efficient filter technology

For general cleaning of the workshop and plant. Bag filter with manual filter cleaning, suitable for the suction extraction of carcinogenic dusts. Run-out collection tank.

Technical data for the series RI 131

Suction unit type	RI 131 EC 2.2	RI 131 W2 G	RI 131 W2 E	RI 131 W3 G
Output [kW]	2,2	2,2	2,6	3,0
Voltage [V]	230	230	230	230
Max. vacuum [kPa]	22	22	23	22
Max. air flow rate [Nm ³ /h]	360	360	430	540
Sound level dB [A]	72	75	76	76
Dimensions [mm]	860 x 670 x 1210	860 x 670 x 1210	860 x 670 x 1210	860 x 670 x 1260
Weight [kg]	78	78	79	82
Article number	990 1098	990 0337	990 0916	990 1045