



Product information RI 332 d.c. suction unit

- » soundproofed d.c. drive unit with direct drive side-channel compressor
- » non-wearing, suitable for multiple shift operation
- » high-quality filter technology in class "M", optionally available up to "H14"

Features



Optional: emptying by tipping with frame



100l run-out collection tank



High-quality bag filter



Lowerable steel collection tank 100l, mobile, handle, pressure compensating hose, PE round bottom bag with holding-down device for dust-free emptying

RI 332



Industrial suction unit for large quantities of dusts

For the suction extraction of general and carcinogenic dusts as well as particularly dangerous carcinogenic materials. Suitable for employment in dust EX-protection Zones 22 (B1), for toxic materials and dusts.

Technical data for the series RI 332

Suction unit type	RI 332 D1,5-IS-M	RI 332 D3-IS-M	RI 332 D4-IS-M
Output [kW]	1,5	3,0	4,0
Voltage [V]	400	400	400
Max. vacuum [kPa]	21	32	26
Max. air flow rate [Nm ³ /h]	210	320	520
Sound level dB [A]	56	60	62
Dimensions [mm]	910 x 760 x 2.000	910 x 760 x 2.000	910 x 760 x 2.270
Weight [kg]	136	148	167
Article number	990 0156 - M	990 0158 - M	990 0306 - M

